



Section Properties

(Per Foot of Width)

Base Steel Thickness (in.)	Weight G90 (psf)	Yield Stress (ksi)	Section Modulus		Deflection Moment of Inertia Mid Span (in ⁴)	Specified Web Crippling Data (lb)			
			Mid Span (in ³)	Support (in ³)		End Pe1	End Pe2	Interior Pi1	Interior Pi2
0.0120	0.64	33	0.0221	0.0202	0.0144	20.4	5.10	40.6	6.90
0.0135	0.71	80	0.0227	0.0203	0.0152	57.0	14.3	113	19.2
0.0180	0.93	33	0.0381	0.0361	0.0227	49.3	12.3	97.0	16.5
0.0240	1.22	33	0.0550	0.0498	0.0302	91.4	22.9	179	30.4
0.0300*	1.51	33	0.0683	0.0637	0.0376	147	36.7	286	48.5

*Only available in 30" coverage.

Live Load Factor = 1.5; Importance Factor (I_{S-SLS}) = 0.90; Importance Factor (I_{S-ULS}) = 1.0

Load Table

Maximum Specified Uniformly Distributed Loads in psf

Span (ft.)		1-Span Base Steel Thickness (in.)					2-Span Base Steel Thickness (in.)					3-Span Base Steel Thickness (in.)				
		0.0120	0.0135	0.0180	0.0240	0.0300	0.0120	0.0135	0.0180	0.0240	0.0300	0.0120	0.0135	0.0180	0.0240	0.0300
1'-4"	S	164	364	283	408	507	150	325	268	370	473	188	406	335	463	591
	D	588	620	927	1234	1540	1411	1488	2224	2961	3695	1111	1172	1751	2331	2910
1'-8"	S	105	233	181	261	324	96	208	172	237	303	120	260	215	296	378
	D	301	317	474	632	788	722	762	1139	1516	1892	569	600	897	1194	1490
2'-0"	S	73	162	126	182	225	67	144	119	164	210	84	180	149	206	263
	D	174	184	275	366	456	418	441	659	877	1095	329	347	519	691	862
2'-6"	S	47	104	80	116	144	43	92	76	105	135	53	115	95	132	168
	D	89	94	141	187	234	214	226	337	449	561	169	178	266	354	441
3'-0"	S	32	72	56	81	100	30	64	53	73	93	37	80	66	91	117
	D	52	54	81	108	135	124	131	195	260	324	98	103	154	205	255
3'-6"	S	24	53	41	59	74	22	47	39	54	69	27	59	49	67	86
	D	32	34	51	68	85	78	82	123	164	204	61	65	97	129	161
4'-0"	S	18	40	31	45	56	17	36	30	41	53	21	45	37	51	66
	D	22	23	34	46	57	52	55	82	110	137	41	43	65	86	108
4'-6"	S	14	32	25	36	44	13	29	24	32	42	16	36	29	41	52
	D	15	16	24	32	40	37	39	58	77	96	29	30	46	61	76
5'-0"	S	12	26	20	29	36	11	23	19	26	34	13	29	24	33	42
	D	11	12	18	23	29	27	28	42	56	70	21	22	33	44	55
5'-6"	S			17	24	30		19	16	22	28	11	24	20	27	35
	D			13	18	22		21	32	42	53	16	17	25	33	41
6'-0"	S			14	20	25		16	13	18	23		20	17	23	29
	D			10	14	17		16	24	32	41		13	19	26	32
6'-6"				17	21			14	11	16	20		17	14	19	25
				11	13			13	19	26	32		10	15	20	25
7'-0"				18				12		13	17			12	17	21
				11				10		20	26			12	16	20

Notes:

- Steel conforms to ASTM A653.
- Section properties are in accordance with CSA-S136-07.
- Values in row "S" are based on strength.
- Values in row "D" are based on a deflection limit of 1/180 of the span.
- Web crippling not included in strength values. See example calculation in notes to designer.
- Contact the sales department for stocked colours and gauges.
- The load table contained on this data sheet was prepared by Dr. R.M. Schuster P.Eng. Professor Emeritus of Structural Engineering, University of Waterloo, Ontario, Canada.

