
# **Polycarbonate Panels**

## **Polycarbonate Century Rib Panels**



**FEATURES:** 

- Clear Polycarbonate UV Resistant Panel
- 10 Year Limited Warranty on yellowing or loss of light transmission
- A correct match for Agway's Century Rib roofing profile, providing up to 90% light transmission
- 20 times the impact resistance of fiberglass of equal thickness
- Resists breaking or cracking due to hail, wind and accidental impact

APPLICATIONS: Agricultural Growing Areas, Seeding Frames, Skylights,

Riding Arenas, any requirements for "Glass-like" uses

SHEET SIZES: Sheet: 38" x 12' with Coverage of 36". Thickness: 0.8 mm (0.032")


STORAGE: Acclimate panels for 24 hours prior to installation. Panels must be stored flat and out of rain or sun.

INSTALLATION: Pre-drill holes 1/8" larger than screws. Fasten on 24" centres on wood

structure. Maintain a minimum roof pitch of 3/12. Bends to gentle curves.

**ACCESSORIES:** Large Tab Century Foam Closures c/w tape

#### **Profiled Polycarbonate Panels**



**FEATURES:** 

- Polycarbonate UV Resistant Panel, in Clear or Solar Grey
- 10 Year Limited Warranty on yellowing or loss of light transmission
- 20 times the impact resistance of fiberglass of equal thickness
- Resists breaking or cracking due to hail, wind and accidental impact
- Condensation control allows water to form a thin sheet rather than droplets

APPLICATIONS: Agricultural Growing Areas, Seeding Frames, Skylights, Riding Arenas, any requirements for "Glass-like" uses

SHEET SIZES:

Clear: 50" x 8', 12', 16'. Coverage: 48". Material Thickness: 0.79 mm (0.031") Solar Grey: 50" x 12'. Coverage: 48". Material Thickness: 0.79 mm (0.031")

STORAGE: Panels must be stored flat and out of rain or sun.


INSTALLATION:

Pre-drill holes 1/8" larger than screws. Fasten on 24" centres on wood structure. Can be curved; please ask for details. Minimum roof pitch: 3/12

ACCESSORIES: 36" Foam Closures (no adhesive)

# Polycarbonate Clear Ridge Cover

### **Polycarbonate Clear Ridge Cover**



**FEATURES**:

- Clear Polycarbonate UV Resistant Ridge Cover
- · Cuts out 98% of UV light
- 10 Year Limited Warranty on yellowing or loss of light transmission
- Up to 90% light transmission
- 20 times the impact resistance of fiberglass of equal thickness with a low temperature extreme of -40°C (-40°F)
- Resists breaking or cracking due to hail, wind and accidental impact
- Provides soft, diffused natural light for farm and industrial buildings
- · An ideal way to supplement artificial lighting

APPLICATIONS: Ridge Closure for use with any configuration of metal roofing when used with

the correct closure strip

SHEET SIZES: 23 1/4" wide x 10' lengths. Material Thickness: 1.25 mm (0.050")

