

PLATINUM HT-B Underlayment

Technical Data



FEATURES:

- Self-Adhering without Heat or Special Adhesives
- Low Installation Temperature: 32°F (0°C) and above
- Nail Sealable - meets and exceeds ASTM D1970
- UV Resistance provides up to 180 days exposure
- No VOCs and chemically compatible with EPDM and TPO products
- Unique Black Butyl adhesive - premium bond to plywood or OSB decks
- GRIPSPOT™ Slip-resistant walking surface
- Ideal for use under metal roofing
- Longer shelf life - 18 months +
- For Limited Lifetime Warranty & Safety Data Sheet, see: agwaymetals.com



PLATINUM HT-B Roll Specifications		
Length per Roll / Width per Roll		67 ft. (20.4 m) / 36" (914 mm)
Weight per Roll / Roll Size		40 lbs (18 kg) / 2 Sq (18.6 m ²)
Rolls per Pallet (48" x 48") / Pallet Weight		36 / 1,440 lbs (654.6 kg)
Rolls per Truckload (28 Skids)		1008
PLATINUM HT-B Technical Data		
TEST & STANDARD		TYPICAL VALUES
Colour		Blue
Walking Surface		GRIPSPOT™ Slip Resistant
Release Liner		Silicone treated, split-release
Nail Sealability	ASTM D1970	Pass
Permeability	ASTM E96	<0.05 perms
Minimum Thickness	ASTM D1970	41 mil (1.04 mm)
Elongation	ASTM D1970	>90%
Lap Seam, Waterproof Integrity	ASTM D1970	Pass
Tensile strength MD/CD	ASTM D1970	MD 120 lbf/in / CD 110 lbf/in
Installation Temperature		32°F (0°C) and above
Thermal Stability	ASTM D1970	265°F (129.4°C) Pass
Low Temp. Flexibility	ASTM D1970	Pass
Tear Resistance MD/CD	ASTM D1970	MD 140 lb/ft / CD 120 lb/ft
Adhesion to Plywood	ASTM D1970	55 lbs/ft @ 75°F (23°C) / 23 lbf/ft @ 40°F (4.4°C)
Adhesion to Galvanized Metal	ASTM D1970	67 lbs/ft @ 75°F (23°C) / 51 lbf/ft @ 40°F (4.4°C)
UV Resistance		180 days
Limited Warranty		Lifetime

